




## QL Electra

Extrem krachtige ronde LED opbouw downlight met hoog rendement (LOR 90%). Voorzien van trompetvormige darklight reflector van hoogglans 99,98% aluminium met brede bundel (> 60°). Zeer lage verblinding (UGR 17) en minimale helderheid door uniek darklight reflector ontwerp. Voorzien van passieve waterkoeling met heat pipe. Wit gelakte (RAL 9003) metalen behuizing en aluminium sierrand (optioneel zilver grijs). Wordt geleverd inclusief interne driver met mogelijkheid tot doorlussen. Directe aansluiting op netspanning. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80). Kleur stabiliteit, MacAdam <3. Vijf jaar garantie.

Extremely powerful round surface mounted LED downlight with high efficacy (LOR 90%). Trumpet shaped darklight reflector made of 99,98% anodised specular aluminium with wide beam angle (> 60°). Very low glare (UGR 17) and minimal brightness due to unique darklight reflector design. Internal passive water cooling with heat pipe technology. White (RAL9003) painted sheet metal housing and die cast aluminium bezel (optionally silver grey). Delivered including internal driver with possibility for through-wiring. Direct connection to mains. Low maintenance and long life expectancy (50.000 hours L80). Colour stability, MacAdam <3. Fast and easy mounting. Five years warranty.



Vermogen Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	Gewicht (kg) Weight (kg)	Artikel nr. Article no.	Dali Dali
17w	3000k	2465	350	2,6	MH01723030	MH01723031
25w	3000k	3435	500	2,6	MH02523030	MH02523031
36w	3000k	4720	700	2,6	MH03623030	MH03623031
46w	3000k	5635	900	2,6	MH04623030	MH04623031
54w	3000k	6455	1050	2,6	MH05423030	MH05423031
62w	3000k	7225	1200	2,6	MH06223030	MH06223031
70w	3000k	7880	1300	2,6	MH07023030	MH07023031
17w	4000k	2510	350	2,6	MH01723040	MH01723041
25w	4000k	3530	500	2,6	MH02523040	MH02523041
36w	4000k	4870	700	2,6	MH03623040	MH03623041
46w	4000k	5830	900	2,6	MH04623040	MH04623041
54w	4000k	6650	1050	2,6	MH05423040	MH05423041
62w	4000k	7450	1200	2,6	MH06223040	MH06223041
70w	4000k	8130	1300	2,6	MH07023040	MH07023041

\*Lichtstroom van armatuur, tolerantie van +/- 10%

\*Luminaire luminous flux, tolerance +/- 10%




Accessoires:  
op aanvraag

Accessories:  
on request

Opties:  
- 2700k  
- 90CRI of 97CRI  
- Schuinstelling voor aflopende plafonds

Opties:  
- 2700k  
- 90CRI or 97CRI  
- Diagonal attachment for sloped ceilings



MH02523040  
25w 4000k 4300lm  
ηLB 82,1%