



**CITILED**  
The Light Engine

## QL Pandora

Geavanceerd pendelarmatuur geschikt voor winkels, showrooms, industriehallen en magazijnen. Passieve koeling in volledig zwart gelakte aluminium behuizing. Verkrijgbaar in verschillende vermogens en bundelbreedtes van 45°, 90° of 120° met polycarbonaat of aluminium reflector. Zeer goed toepasbaar in hoge ruimtes waar veel licht op werkniveau vereist is.

Dimbare driver die aansluit op het design van het koelelement. Het koelelement is voorzien van een heatpipe om de lichtbron optimaal te koelen. Directe aansluiting op netspanning. Snelle en eenvoudige montage door middel van enkelvoudig montagepunt. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L70 B20 @ 25°C). Vijf jaar garantie.

Advanced pendant luminaire suitable for shops, showrooms, industrial halls and warehouses. Passive cooling in fully black painted aluminum housing. Available in different wattages and beam angles of 45°, 90° or 120° with polycarbonate or aluminum reflector. Very well applicable in high spaces where high luxlevels are required at work level.

Dimmable driver that fits the design of the cooling element. The heatsink is equipped with a heatpipe to optimally cool the light source. Direct connection to the mains. Fast and easy installation by single mounting point. Low maintenance and high life expectancy (50,000 hours L70 B20 @ 25° C). Five year warranty.

Vermogen Watts	Kleur Colour	Reflector Reflector	Beam Beam	Lumen Lumen	CRI (Ra) CRI (Ra)	Diameter (mm) Diameter (mm)	Hoogte (mm) Height (mm)	Artikel nummer Article no.
100W	4000k	PC	45°	11.600	>80	410	465	TG10023040
100W	4000k	AL	45°	12.100	>80	415	455	TG10023041
100W	4000k	AL	90°	12.500	>80	515	385	TG10023042
100W	4000k	AL	120°	12.400	>80	495	345	TG10023043
150W	4000k	PC	45°	16.800	>80	410	465	TG15023040
150W	4000k	AL	45°	17.700	>80	415	455	TG15023041
150W	4000k	AL	90°	18.300	>80	515	385	TG15023042
150W	4000k	AL	120°	18.100	>80	495	345	TG15023043
250W	4000k	PC	45°	25.500	>80	410	515	TT25023040
250W	4000k	AL	45°	27.000	>80	415	505	TT25023041
250W	4000k	AL	90°	27.700	>80	515	435	TT25023042
250W	4000k	AL	120°	27.600	>80	495	395	TT25023043

### Opties:

- CCT 3000K - 5000K
- Andere vermogens op aanvraag

### Optional:

- CCT 30000K - 5000K
- Different wattages on request

### Toepassingen:

- Productiehallen
- Magazijnen
- Winkels

### Applications

- Production facilities
- Storage locations
- Retail shops