




QL Rosandra

Slagvast water- en stofdicht IP65 LED armatuur met opalen afscherming (optioneel helder). Zeer hoog armatuur rendement (>118lm/w). Glasvezelversterkte behuizing (polyester) en diffuser uit PC met RVS clips voor sluiting. Binnenreflector uit wit gelakt plaatstaal. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80) of (65.000 uur L70 Ta. Max. (zie tabel) + 6°C. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie (Ta.Max -20°C).

Impact resistant water- and dust proof IP65 luminaire with high voltage LEDs. Fiberglass reinforced polyester housing, opal PC diffuser (optionally clear) and stainless steel clips. Inner reflector plate made of white painted sheet metal. High luminaire efficiency (118lm/w). Low maintenance and long life expectancy 50.000 hours L80 or 65.000 hours L70 Ta. Max. (see table) +6°C. Colour stability, Mac Adam <3. Warranty 5 years (Ta. Max. -20°C).


Vermogen Power	Kleur Colour	Lumen Lumen	CRI (Ra) CRI (Ra)	Lengte (mm) Length (mm)	Breedte (mm) Width (mm)	Hoogte (mm) Height (mm)	clips Clips	Ta.Max Ta.Max	 kg	Noodvoorz. (h) Emergency (h)	Art. nummer Art. no.	1-10V 1-10V	Dali Dali
18w	3000k	2110	>80	665	134	99	6	40	2	1/3	MA01823030	MA01823031	MA01823032
27w	3000k	3000	>80	665	134	99	6	30	2	1/3	MA02723030	MA02723031	MA02723032
22w	3000k	2480	>80	1275	134	99	8	40	2,9	1/3	MA02223030	MA02223031	MA02223032
34w	3000k	4220	>80	1275	134	99	8	40	2,9	1/3	MA03423030	MA03423031	MA03423032
51w	3000k	5990	>80	1275	134	99	8	30	2,9	1/3	MA05123030	MA05123031	MA05123032
32w	3000k	3580	>80	1575	134	99	10	40	3,8	1/3	MA03223030	MA03223031	MA03223032
42w	3000k	5230	>80	1575	134	99	10	40	3,8	1/3	MA04223030	MA04223031	MA04223032
64w	3000k	7400	>80	1575	134	99	10	30	3,8	1/3	MA06423030	MA06423031	MA06423032
18w	4000k	2220	>80	665	134	99	6	40	2	1/3	MA01823040	MA01823041	MA01823042
27w	4000k	3160	>80	665	134	99	6	30	2	1/3	MA02723040	MA02723041	MA02723042
22w	4000k	2610	>80	1275	134	99	8	40	2,9	1/3	MA02223040	MA02223041	MA02223042
34w	4000k	4440	>80	1275	134	99	8	40	2,9	1/3	MA03423040	MA03423041	MA03423042
51w	4000k	6300	>80	1275	134	99	8	30	2,9	1/3	MA05123040	MA05123041	MA05123042
32w	4000k	3760	>80	1575	134	99	10	40	3,8	1/3	MA03223040	MA03223041	MA03223042
42w	4000k	5500	>80	1575	134	99	10	40	3,8	1/3	MA04223040	MA04223041	MA04223042
64w	4000k	7790	>80	1575	134	99	10	30	3,8	1/3	MA06423040	MA06423041	MA06423042

Opties:

- PC clips
- RVS ophangbeugel
- IP65 Wieland/Stucchi connector
- 5000k, 6500k
- Bewegingssensor (niet voor 655 mm)
- Doorvoerbedrading
- CRI >90

Optional:

- PC clips
- Stainless steel suspension bracket
- IP65 Wieland/Stucchi connector
- 5000k, 6500k
- Motion sensor (not for 665mm)
- Through-wiring
- CRI >90



MA03223030
32w 3580lm 3000k
ηLB 100%

