




QL Albireo S

Faretto cilindrico con altezza per il montaggio poco profonda (99 millimetri). Riflettore darklight a forma conica, di alluminio speculare 99,98% con ampio angolo di fascio (> 77°). Abbagliamento molto basso (UGR <18) e luminosità minima dovuta al design unico del riflettore darklight. Corpo in alluminio pressofuso verniciato bianco (RAL9003). Con driver interno e possibilità per cablaggio passante. Collegamento diretto alla rete. Bassa manutenzione e durata elevata (50.000 ore L80). Stabilità di colore, Mac Adam <3. Montaggio facile e veloce. Cinque anni di garanzia.

Round LED downlight with shallow build-in height (99mm). Trumpet shaped darklight reflector made of 99,98% specular aluminium with wide beam angle (> 77°). Very low glare (UGR <18) and minimal brightness due to unique darklight reflector design. White painted die cast aluminium body (RAL9003). Delivered including internal driver with possibility for through-wiring. Direct connection to mains. Low maintenance and high life expectancy (50.000 hours L80). Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.



Potenza Watts	Colore Colour	Lumen* Lumen*	Ampere (mA) Amperage (mA)	kg	Emergenza (u) Emergency (h)	Art. Article no.	Dimmerabile (1-10V) Dimmable (1-10V)	Dali
9w	3000k	1135	250	1,3	1/3	MS00923130	MS00923131	MS00923132
13w	3000k	1515	350	1,3	1/3	MS01323130	MS01323131	MS01323132
18w	3000k	2060	500	1,3	1/3	MS01823130	MS01823131	MS01823132
25w	3000k	2960	700	1,3	1/3	MS02523130	MS02523131	MS02523132
9w	4000k	1165	250	1,3	1/3	MS00923140	MS00923141	MS00923142
13w	4000k	1555	350	1,3	1/3	MS01323140	MS01323141	MS01323142
18w	4000k	2125	500	1,3	1/3	MS01823140	MS01823141	MS01823142
25w	4000k	3070	700	1,3	1/3	MS02523140	MS02523141	MS02523142

*Flusso luminoso dell'apparecchio, tolleranza +/- 10%

*Luminaire luminous flux, tolerance of +/- 10%




Accessori:

- GST18i3 splitter
- BST14i2 splitter
- 2700k
- 90CRI oppure 97CRI
- Attacco per soffitti inclinati a richiesta

Accessories:

- GST18i3 splitter
- BST14i2 splitter
- 2700k
- 90CRI or 97CRI
- Diagonal attachment for sloped ceilings on request



MS01323040
13w 4000k 1850lm
ηLB 84,0%