

QL Arques

Apparecchio lineare compatto multifunzionale a LED dalla luce confortevole. Con LED ad alta tensione e molto efficienti (> 167lm / w). Alloggiamento in alluminio estruso grigio anodizzato. Disponibile con due angoli di fascio a 90° (UGR <20) e 60°(UGR <17). Con diffusore a microprismi che riduce la luminosità a L <1000cm / m2 e ha un angolo di emissione > 65°. Molto adatto nei negozi, supermercati e spazi per lavorazioni di precisione. Minima manutenzione e durata elevata (50.000 ore L80). Stabilità di colore, MacAdam <3. Montaggio facile e veloce. Cinque anni di garanzia.

Multifunctional compact linear surface mounted LED luminaire with comfortable light. With high voltage and high efficiency LED lines (>167lm/w). Housing made grey anodised extruded aluminium. Available in two beam angles 90 degree (UGR<20) and 60 degrees (UGR<17). With micro prism diffuser that reduces brightness to under L<1000cm/m2 and has an emission angle >65°. Very suitable for shops, supermarkets and production areas with fine work. Low maintenance and long life expectancy (50.000 hours L80). Colour stability, MacAdam <3. Fast and easy mounting. Five years warranty.




Potenza Watts	Colore Colour	Lumen Lumen	Fascio Beam angle	CRI (Ra) CRI (Ra)	Lunghezza Length (mm)	Larghezza Width (mm)	Altezza (mm) Height (mm)	kg	Emergenza (h) Emergency (h)	Art. Article no.	Dali Dali
22w	3000k	2130	60	>80	1179	100	76	3,3	1/3	MS02223030	MS02223031
34w	3000k	3070	60	>80	1179	100	76	3,3	1/3	MS03423030	MS03423031
52w	3000k	5400	60	>80	1179	100	76	3,7	1/3	MS05223030	MS05223031
22w	3000k	2125	90	>80	1179	100	76	3,3	1/3	MS02223130	MS02223131
34w	3000k	3100	90	>80	1179	100	76	3,3	1/3	MS03423130	MS03423131
52w	3000k	4250	90	>80	1179	100	76	3,7	1/3	MS05223130	MS05223131
28w	3000k	2660	60	>80	1479	100	76	3,3	1/3	MS02823030	MS02823031
43w	3000k	3840	60	>80	1479	100	76	3,3	1/3	MS04323030	MS04323031
65w	3000k	5320	60	>80	1479	100	76	3,7	1/3	MS06523030	MS06523031
28w	3000k	2660	90	>80	1479	100	76	3,3	1/3	MS02823130	MS02823131
43w	3000k	3840	90	>80	1479	100	76	3,3	1/3	MS04323130	MS04323131
65w	3000k	5320	90	>80	1479	100	76	3,7	1/3	MS06523130	MS06523131
22w	4000k	2220	60	>80	1179	100	76	3,3	1/3	MS02223040	MS02223041
34w	4000k	3210	60	>80	1179	100	76	3,3	1/3	MS03423040	MS03423041
52w	4000k	4445	60	>80	1179	100	76	3,7	1/3	MS05223040	MS05223041
22w	4000k	2220	90	>80	1179	100	76	3,3	1/3	MS02223140	MS02223141
34w	4000k	3210	90	>80	1179	100	76	3,3	1/3	MS03423140	MS03423141
52w	4000k	4445	90	>80	1179	100	76	3,7	1/3	MS05223140	MS05223141
28w	4000k	2775	60	>80	1479	100	76	3,3	1/3	MS02823040	MS02823041
43w	4000k	4020	60	>80	1479	100	76	3,3	1/3	MS04323040	MS04323041
65w	4000k	5555	60	>80	1479	100	76	3,7	1/3	MS06523040	MS06523041
28w	4000k	2775	90	>80	1479	100	76	3,3	1/3	MS02823140	MS02823141
43w	4000k	4020	90	>80	1479	100	76	3,3	1/3	MS04323140	MS04323141
65w	4000k	5555	90	>80	1479	100	76	3,7	1/3	MS06523140	MS06523141

*Flusso luminoso dell'apparecchio, tolleranza +/- 10%

*Luminaire luminous flux, tolerance of +/- 10%

Opzioni:
- 5000k oppure 6500k
- 90CRI

Optional:
- 5000k or 6500k
- 90CRI



MS05223030
52W 5400lm 3000k 60°
ηLB 59%

